



## SPECIFICATIONS

### TwoStroke: 6-15 hp



<b>HP / kW</b>	9.9 / 7.2
<b>Engine type</b>	Inline 2
<b>Displacement (CID/CC)</b>	10.3 / 169
<b>Cylinder Configuration</b>	I-2
<b>Full throttle RPM</b>	5000 - 6000
<b>Fuel induction system</b>	Loop-charged (1 carb)
<b>Alternator amp / Watt</b>	7 amp / 80 watt
<b>Recommended fuel</b>	Pre-Mix 50:1
<b>Recommended oil</b>	2-Cycle TC-W3
<b>Starting</b>	Electric Manual
<b>Steering</b>	Remote Tiller
<b>Shaft length</b>	15" / 381 mm 20" / 508 mm
<b>Gearcase ratio</b>	2.08:1
<b>Dry weight *Lightest model available</b>	26 kg
<b>Bore and stroke</b>	50mm x 43mm
<b>Ignition</b>	CDI w/electronic spark advance
<b>Fuel system</b>	Carbureted
<b>Cooling system</b>	Water-cooled with thermostat
<b>Gear shift</b>	F-N-R
<b>Trim system</b>	6 position Manual
<b>Exhaust system</b>	Through prop
<b>Shallow water trim range (degrees)</b>	20
<b>Remote fuel tank standard (gal / L)</b>	3.2 / 12
<b>Color</b>	Phantom Black
<b>Lubrication system</b>	Pre-Mix
<b>Oil Injection</b>	Pre-mix

© 2017 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of Brunswick Corporation.