



## SPECIFICATIONS

### Verado®: Six Cylinder 225-350 hp



<b>HP / kW</b>	350 / 261
<b>Engine type</b>	Inline 6
<b>Displacement (L)</b>	2.6
<b>Full throttle RPM</b>	5800-6400
<b>Air induction</b>	Supercharged with charge air cooling and electronic boost pressure control
<b>Fuel induction system</b>	Sequential multi-port electronic fuel injection (EFI)
<b>Alternator amp / Watt</b>	70 amp / 882 watt (Belt-Driven)
<b>Recommended fuel</b>	Unleaded Regular 89 Octane Minimum (R+M)/2 or 93 RON Unleaded 91 Octane or 95 RON for premium performance in all conditions 10% Ethanol Maximum
<b>Recommended oil</b>	Mercury FourStroke 25W40 Marine Oil
<b>Engine protection operator warning system</b>	SmartCraft Engine Guardian
<b>Compatible with SmartCraft digital technology</b>	Yes
<b>Starting</b>	Smart Start Electric
<b>Controls</b>	SmartCraft Digital
<b>Steering</b>	Electro-hydraulic power steering
<b>Shaft length</b>	20" / 508 mm 25" / 635 mm 30" / 762 mm
<b>Gearcase ratio</b>	1.75:1
<b>Dry weight *Lightest model available</b>	668 lbs / 303 kg
<b>CARB star rating</b>	2
<b>Gearcase options</b>	5.44"
<b>Trim system</b>	Power trim and tilt with SmartCraft programmable tilt
<b>Counter Rotation</b>	Available
<b>Color</b>	Cold Fusion White Pearl Fusion White Phantom Black Warm Fusion White

© 2017 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of Brunswick Corporation.